



1x2 (2x2) Ultra-Low PDL Broadband Splitter

Features of our splitter:

- Ultra-Low PDL
- Low Insertion loss
- High Directivity
- Stable and Reliable

Applications for our splitter:

- Optical Communications System
- Optical Testing System
- Optical Fiber Sensor
- Optical Power Distributor

Specifications:

Specification		Splitting Ratio: 50:50	
Parameter		Unit	Premium A grade
Port Configuration			1x2 or 2x2
Bandwidth		nm	+/-40
Insertion Loss	Max.	dB	3.4 3.6
Excess loss	Typ.	dB	0.07 0.1
Uniformity	Max.	dB	0.6 1.0
PDL	Max.	dB	0.05 0.07
Return Loss *	Min.	dB	50
Operating Temperature		°C	-40 to +85
Storage Temperature		°C	-50 to +85
Package Type		mm	S6 Diam. 3x54: for bare fiber
			S8 Diam. 3x70: for 0.9mm loose tube
			M1 10x20x90: for 0.9mm loose tube or 3mm cable

* >60dB on request for 1x2 structure

Splitting Ratio and Insertion Loss Conversion Table				
Splitting Ratio	Maximum Insertion Loss (dB)			
	Premium		A Grade	
Output Port	Output Port	Output Port 2	Output Port 1	Output Port 2



Output Port	Output Port 1	Output Port 2	Output Port 1	Output Port 2
50:50	3.4	3.4	3.6	3.6
60:40	2.5	4.4	2.8	4.8
70:30	1.8	5.6	2.0	6.1
80:20	1.1	7.4	1.3	8.0
90:10	0.6	10.8	0.8	12

Ordering Information:

- Wavelength: 1625, 1590, 1570, 1550, 1480, 1475, 1310
- Structure: 1x2, 2x2
- Splitting Ratio: 90:10, 80:20, 70:30, 60:40, 50:50
- Grade: Premium (P), A grade
- Fiber type: SMF-28
- Pigtail: 250um bare fiber, 0.9mm loose tube, 3mm cable
- Fiber length: 0.5m, 1.0m, 1.5m, 2.0m
- Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com