



HI1060 Flex Fiber 980/C+L Band WDM

Features of our WDM:

- Ultra-Low PDL
- Ultra-Low Insertion loss
- High Isolation
- High Return Loss
- Stable and Reliable

Applications for our WDM:

- Optical Communications System
- Optical Fiber Amplifier
- EDFA Module

Specifications:

Specification			980/C+L Band	
Parameter	Unit		Premium	A grade
Shorter Wavelength Channel	nm		960 to 990	
Insertion Loss	Max.	dB	0.05	0.1
PDL	Max.	dB	0.01	0.02
Isolation @C+L Band	Min.	dB	15	14
Longer Wavelength Channel	nm		C+L Band (1528 to 1605)	
Insertion Loss	Max.	dB	0.15	0.25
PDL	Max.	dB	0.02	0.03
Isolation @960 to 990	Min.	dB	20	18
Return Loss	Min.	dB	50	
Operating Temperature	°C		-40 to +85	
Storage Temperature	°C		-50 to +85	
Package Type	mm		S6	Diam. 3x54: for bare fiber
			S8	Diam. 3x70: for 0.9mm loose tube
			M1	10x20x90: for 0.9mm loose tube



		M1	10x20x90: for 0.9mm loose tube or 3mm cable
--	--	----	--

Ordering Information:

- Wavelength: 980/C+L Band
- Structure: 1x2 or 2x2
- Grade: Premium (P) or A grade
- Fiber type: HI1060Flex
- Pigtail: 250um bare fiber, 0.9mm loose tube, 3mm cable
- Fiber length: 0.5m, 1.0m, 1.5m, 2.0m, customer's request
- Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com