



980/1060 SM WDM

Features of our WDM:

- Low PDL
- Low Insertion loss
- High Isolation
- High Return loss
- Stable and Reliable

Applications for our WDM:

- Optical Communications System
- Optical Fiber Amplifier
- EDFA Module

Specifications:

Specifications				
Parameter		Unit	Premium	A grade
Shorter wavelength channel		nm	980+/-5	
Insertion loss	Max.	dB	0.3	0.4
PDL	Max.	dB	0.1	0.15
Isolation @1060+/-5	Min.	dB	15	13
Longer Wavelength Channel		nm	1060+/-5	
Insertion Loss	Max.	dB	0.3	0.4
PDL	Max.	dB	0.1	0.15
Isolation @980+/-5	Min.	dB	15	13
Return Loss	Min.	dB	50	
Operating Temperature		°C	-40 to +85	
Storage Temperature		°C	-50 to +85	
Package Type		mm	S9	Diam. 3x76: for bare fiber
			S10	Diam. 3x92: for 9um loose tube
			M3	Diam. 7.5x18x100 for 9um loose tube or 3mm cable

Ordering Information:



Ordering Information:

- Wavelength: 980/1060nm
- Structure: 1x2 or 2x2
- Grade: Premium (P) or A grade
- Fiber type: HI980, HI1060, HI1060 Flex, OFS BF05635-02
- Pigtail: 250um bare fiber, 0.9mm loose tube, 3mm loose tube
- Fiber length: 0.5m, 1.0m, 1.5m, 2.0m, customer's request
- Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com