



HI1060 Flex Fiber 980/C or L Band WDM

Features of our WDM:

- Ultra-Low PDL
- Ultra-Low Insertion loss
- High Isolation
- High Return Loss
- Stable and Reliable

Applications for our WDM:

- Optical Communications System
- Optical Fiber Amplifier
- EDFA Module

Specifications:

Specification			980/C or L Band	
Parameter		Unit	Premium	A grade
Shorter Wavelength Channel		nm	960 to 990	
Insertion Loss	Max.	dB	0.05	0.1
PDL	Max.	dB	0.01	0.02
Isolation @C or L Band	Min.	dB	20	18
Longer Wavelength Channel		nm	C Band (1528 to 1605) or L Band (1570 to 1605)	
Insertion Loss	Max.	dB	0.05	0.1
PDL	Max.	dB	0.01	0.02
Isolation @960 to 990	Min.	dB	20	18
Return Loss	Min.	dB	50	
Operating Temperature		°C	-40 to +85	
Storage Temperature		°C	-50 to +85	
Package Type		mm	S6	Diam. 3x54: for bare fiber
			S8	Diam. 3x70: for 0.9mm loose tube



		M1	10x20x90: for 0.9mm loose tube or 3mm cable
--	--	----	--

Ordering Information:

- Wavelength: 980/C or L Band

Structure: 1x2 or 2x2

Grade: Premium (P) or A grade

Fiber type: HI1060Flex

Pigtail: 250um bare fiber, 0.9mm loose tube, 3mm cable

Fiber length: 0.5m, 1.0m, 1.5m, 2.0m, customer's request

Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com