



HI980 980/C or L Band WDM

Features of our WDM:

- Low PDL
- Low Insertion loss
- High Return Loss
- Stable and Reliable

Applications for our WDM:

- Optical Communications System
- Optical Fiber Amplifier
- EDFA Module

Specifications:

Specification		980/C or L Band	
Parameter	Unit	Premium	A grade
Shorter Wavelength Channel	nm	960 to 990	
Insertion Loss	Max. dB	0.3	0.4
PDL	Max. dB	0.05	0.05
Isolation @C or L Band	Min. dB	20	18
Longer Wavelength Channel	nm	C Band (1530 to 1565) L Band (1530 to 1565)	
Insertion Loss	Max. dB	0.3	0.4
PDL	Max. dB	0.05	0.05
Isolation @960 to 990	Min. dB	20	18
Return Loss	Min. dB	50	
Operating Temperature	°C	-40 to +85	
Storage Temperature	°C	-50 to +85	
Package Type	mm	S6	Diam. 3x54: for bare fiber
		S8	Diam. 3x70: for 0.9mm loose tube
		M1	10x20x90: for 3mm cable

Ordering Information:

- Wavelength: 980/C or L Band
- Structure: 1x2 or 2x2
- Grade: Premium (P) or A grade
- Fiber type: HI980



- Pigtail: 250um bare fiber, 0.9mm loose tube, 3mm cable
- Fiber length: 0.5m, 1.0m, 1.5m, 2.0m, customer's request
- Connector: none, FC/PC, FC/APC, ST, customer's request

We have unbeatable price for this product.

- Price is updating, please make a request for our most recent price by calling (514) 334-4588 or by emailing sales2@o-eland.com